



XM3250

Reliability. Security. Productivity.



(800) 346-6920 getaos.com



XM3250 with optional trays













This is a Class A device according to the FCC Rules and international electromagnetic emissions standards. This device is not intended for use in residential or domestic environments due to potential interference to radio communications.

#### Lexmark XM3250

The Lexmark XM3250 offers printing at up to 50 pages per minute\*, superior print quality, enhanced security and thoughtfully engineered durability, all powered by a quad-core processor to maximize performance. An optional hard drive and optional integrated stapler add capabilities rarely found on desktop devices.



#### Get more done

- Fax, print, copy and scan with the power of a 1.2 GHz quadcore processor, 2 GB of memory and optional hard drive.
- Get up to 50-page-per-minute printing and scan up to 100 images per minute.
- Intuitive 7-inch e-Task touch screen offers smooth, tabletlike interaction.
- Built-in productivity apps save time and improve efficiency.
- Optional integrated stapler adds finishing capabilities.

## Ready when you are

- ▶ Long-life fuser and imaging components extend uptime.
- Vinison™ Toner replacement cartridges deliver up to 21,000 pages\*\* of high-quality printing.
- Maximum input capacity of 2300 pages means fewer interruptions.
- Durable metal frame is designed for longevity.

### Robust, built-in security

- Lexmark's full-spectrum security architecture helps keep your information safe—on the document, the device, over the network, and everywhere in between.
- A range of embedded features harden device against attacks.
- Go beyond standard Confidential Print with optional security solutions like Print Release.
- Keypoint Intelligence Buyers Lab honored Lexmark with a prestigious BLI PaceSetter award for Document Imaging Security\*\*\*.



### **Built for planet earth**

- Energy management features reduce power consumption in active use or sleep mode.
- Standard two-sided printing saves paper.
- Use of post-consumer recycled content in manufacturing saves natural resources.
- ▶ Device is rated EPEAT® Silver and ENERGY STAR® certified.
- Recycle cartridges through the award-winning Lexmark Cartridge Collection Program (LCCP).

<sup>\*\*</sup>Average yield based on approximately 5% print coverage \*\*\*Award based on North America and/or Western Europe data



<sup>\*</sup>Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

# Lexmark XM3250



4 Staple finisher
7.7 x 16.1 x 14.6\*
195 x 409 x 371.5
\*Adds 2.5 inches of depth to MX622de

Multifunction product with 7-inch (17.8 cm) class touch screen 21.5 x 19.3 x 18.8 inches 545 x 489 x 476.5 mm

2 550-sheet tray 5 x 15.7 x 14.7 inches 126 x 389 x 374 mm

3 250-sheet tray 3.7 x 15.7 x 14.7 inches 95 x 389 x 374 mm



Supports up to three optional trays.

P/N Hardware

36S0940 Lexmark XM3250

P/N Cartridges and supplies

24B6887 Black Lexmark toner cartridge

P/N Paper handling 36S2910 250-sheet tray 36S3110 550-sheet tray

36S3120 550-sheet lockable tray

36S8010 Staple finisher

P/N Memory and hard disk options 57X9801 256 MB user flash memory 27X0400 500 GB hard disk drive (SATA)

P/N Application solutions

40C9200 Forms and bar code card

40C9201 IPDS card 40C9202 PRESCRIBE card

57X9810 Traditional Chinese font card 57X9812 Simplified Chinese font card

57X9814 Korean font card 57X9815 Japanese font card

P/N Connectivity

27X6410 MarkNet N8372 (front wifi - FSM)
27X0900 RS-232C serial interface card
27X0901 Parallel 1284-B Interface Card

27X0912 MarkNet N8230 fiber ethernet 100BASE-FX(LC),

1000BASE-SX(LC)

1021231 Parallel cable (10 ft.) 1021294 UB 2.0 cable (2 meter)

P/N Furniture 3073173 Swivel cabinet

35S8502 Adjustable printer stand

P/N User replaceable parts
41X1324 DADF Flatbad cushion
41X1239 Optional pick tray roller
41X1325 DADF Separator roller
41X1326 DADF Pick roller

41X1198 Standard 550 pick tray roller

© 2018 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. AirPrint and the AirPrint Logo are trademarks of Apple, Inc. ENERGY STAR® is a U.S. registered mark. EPEAT® is a trademark of EPEAT, Inc. in the United States and other countries. Google Cloud Print is a trademark of Google, Inc. MOPRIA®, the Mopria® Logo<sup>™</sup> and the Mopria® Alliance logos are trademarks, service marks, and certification marks of Mopria Alliance, Inc. in the United States and other countries. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (http:// ww.openssl.org/).



Product specifications	Lexmark XM3250
Printing	
Display	Lexmark e-Task 7-inch (17.8 cm) color touch screen
Print Speed: Up to <sup>6</sup>	Black: 50 ppm
Time to First Page: As fast as	Black: 6 seconds
Print Resolution	Black: 1200 Image Quality, 1200 x 1200 dpi, 2400 Image Quality, 600 x 600 dpi
Memory	Standard: 2048 MB / Maximum: 2048 MB
Hard Disk	Option available
Recommended Monthly Page Volume <sup>2</sup>	2000 - 20000 pages
Maximum Monthly Duty Cycle: Up to <sup>3</sup>	175000 pages per month
Copying	
Copy Speed: Up to <sup>6</sup>	Black: 50 cpm
Time to First Copy: As fast as	Black: 6 seconds
Scanning	
Scanner Type / ADF Scan	Flatbed scanner with ADF / DADF (single pass Duplex)
A4/Ltr Duplex Scan Speed: Up to	Black: 94 / 100 sides per minute / Color: 60 / 64 sides per minute
A4/Ltr Simplex Scan Speed: Up to	Black: 47 / 50 sides per minute / Color: 30 / 32 sides per minute
ADF Paper Input Capacity: Up to	100 pages 20 lb or 75 gsm bond
Faxing	
Modem Speed	ITU T.30, V.34 Half-Duplex, 33.6 Kbps
Supplies <sup>7</sup>	
Laser Cartridge Yields (up to) <sup>1</sup>	21,000-page Cartridge
Imaging Unit Estimated Yield: Up to	60000 pages, based on 3 $$ average letter/A4-size pages per print job and $\sim$ 5% coverage
Cartridge(s) Shipping with Product <sup>8</sup>	6,000-page Starter Return Program Toner Cartridge
Paper Handling	
Included Paper Handling	550-Sheet Input, 100-Sheet Multipurpose Feeder, Integrated Duplex, 250-Sheet Output Bin
Optional Paper Handling	250-Sheet Tray, 550-Sheet Tray, 550-Sheet Lockable Tray, Inline Stapler
Paper Input Capacity: Up to	Standard: 650 pages 20 lb or 75 gsm bond / Maximum: 2300 pages 20 lb or 75 gsm bond
Paper Output Capacity: Up to	Standard: 250 pages 20 lb or 75 gsm bond / Maximum: 250 pages 20 lb or 75 gsm bond
Media Types Supported	Card Stock, Envelopes, Paper Labels, Plain Paper, Transparencies, Refer to the Paper & Specialty Media Guide
Media Sizes Supported	10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6
General Information⁴	
Standard Ports	One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified Port (Type A), Rear USB 2.0 Specification Hi-Speed Certified Port (Type A)
Optional Network Ports / Optional Local Ports	Marknet N8372 WiFi Option / Internal RS-232C serial, Internal 1284-B Bidirectional Parallel
Noise Level: Operating	Print: 55 dBA / Copy: 56 dBA / Scan: 55 dBA
Specified Operating Environment	Humidity: 8 to 80% Relative Humidity, Temperature: 10 to 32°C (50 to 90°F), Altitude: 0 - 5000 Meters (16,404 Feet)
Size (in H x W x D) / Weight (lb.)	21.5 x 19.3 x 18.8 in. / 49.2 lb.

All information in this brochure is subject to change without notice. Lexmark is not liable for any errors or omissions.

This is a Class A device according to the FCC Rules and international electromagnetic emissions standards. This device is not intended for use in residential or domestic environments due to potential interference to radio communications.

Average yield based on approximately 5% print coverage. <sup>2</sup>"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. <sup>3</sup>"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. <sup>4</sup>Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details. <sup>5</sup>Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. <sup>6</sup>Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds. <sup>7</sup>Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details. <sup>8</sup>Average Continuous Cartridge Yield in one-sided (simplex) mode 6,000 standard pages. Declared yield value in accordance with ISO/IEC 19752.



